

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 9050 X5 HS Clear Coat

Creation date: 17.12.2013 · Revision: 10.6.2019 · Version: 1

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name

9050 X5 HS Clear Coat



chemius.net/yuBa4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Clear coat

Uses advised against

No information.

1.3. Details of the supplier of the safety data sheet

Manufacturer

SILCO, D.O.O.

Address: Šentrupert 5 a, 3303 Gomilsko, Slovenia

Phone: +386 3 703 3180

Fax: +386 3 703 3188

E-mail: n.cvilak@silco-automotive.com

Point of contact for safety info: Nejc Cvilak

1.4. Emergency telephone number

Emergency

112

Supplier

+386 3 703 3180

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.

STOT SE 3; H336 May cause drowsiness or dizziness.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 9050 X5 HS Clear Coat

Creation date: 17.12.2013 · Revision: 10.6.2019 · Version: 1

2.2 Label elements

2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]



Signal word: **Warning**

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains hydroxyphenyl-benzotriazole derivate I; Hydroxyphenyl-benzotriazole derivate II; Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate. May produce an allergic reaction.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P262 Do not get in eyes, on skin, or on clothing.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P403 + P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with national regulations.

2.2.2. Contains:

n-butyl acetate (CAS: 123-86-4, EC: 204-658-1, Index: 607-025-00-1)

2.2.3. Special provisions

Special hazards are not known or expected.

2.3. Other hazards

No information.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

For mixtures see 3.2.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 9050 X5 HS Clear Coat

Creation date: 17.12.2013 · Revision: 10.6.2019 · Version: 1

3.2. Mixtures

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
n-butyl acetate	123-86-4 204-658-1 607-025-00-1	<38	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066		-
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7	<20	Flam. Liq. 3; H226		01-2119475791-29
2-butoxyethyl acetate	112-07-2 203-933-3 607-038-00-2	<3	Acute Tox. 4; H312 Acute Tox. 4; H332		-
1,4-diazabicyclooctane	280-57-9 205-999-9 -	<0,6	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319		-
acetone	67-64-1 200-662-2 606-001-00-8	0,1-1	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066		-
hydroxyphenyl-benzotriazole derivate I	104810-48-2 - -	0,1-1	Skin Sens. 1; H317 Aquatic Chronic 2; H411		-
2-methylpropan-2-ol	75-65-0 200-889-7 603-005-00-1	0,1-1	Flam. Liq. 2; H225 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H335		-
Hydroxyphenyl-benzotriazole derivate II	104810-47-1 - -	0,1-1	Skin Sens. 1; H317 Aquatic Chronic 2; H411		-
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7 255-437-1 -	0,1-1	Skin Sens. 1; H317 Aquatic Chronic 2; H411		-
Acrylates/methacrylates	- - -	0,01-0,1	Skin Sens. 1; H317		-
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	82919-37-7 280-060-4 -	0,01-0,1	Skin Sens. 1; H317 Aquatic Chronic 2; H411		-

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

General notes

Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency. When in doubt or if feeling unwell seek medical assistance. Show the safety data sheet and label to the physician.

Following inhalation

Remove patient to fresh air - move out of dangerous area. If symptoms develop and persist, seek medical attention.

Following skin contact

Take off all contaminated clothing. Areas of the body that have come into contact with the product must be rinsed with water. If symptoms develop and persist, seek medical attention.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **9050 X5 HS Clear Coat**

Creation date: **17.12.2013** · Revision: **10.6.2019** · Version: **1**

Following ingestion

Do not induce vomiting! Rinse mouth thoroughly with water. In case of doubt or if feeling unwell seek medical help. Show the physician the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Vapours may cause drowsiness and dizziness.

Skin contact

Prolonged and repeated exposure may cause redness, itching and cracking of the skin in sensitive people.

Eye contact

Contact with eyes can cause irritation (redness, tearing, pain).

Ingestion

May cause nausea/vomiting and diarrhea.

4.3. Indication of any immediate medical attention and special treatment needed

-

SECTION 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

-

5.3. Advice for firefighters

Protective actions

In case of fire or heating do not breathe fumes/vapours. Cool containers at risk with water spray. If possible remove containers from endangered area.

Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8).

Emergency procedures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking! Prevent access to unprotected personnel.

6.1.2. For emergency responders

-

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 9050 X5 HS Clear Coat

Creation date: 17.12.2013 · Revision: 10.6.2019 · Version: 1

6.2. Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

6.3. Methods and material for containment and cleaning up

6.3.1. For containment

-

6.3.2. For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor.

6.3.3. Other information

-

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

7.1.1. Protective measures

Measures to prevent fire

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Use spark-proof tools. Take precautionary measures against static discharges.

Measures to prevent aerosol and dust generation

-

Measures to protect the environment

-

7.1.2. Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin and eyes. Do not breathe vapours/mist.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1. Technical measures and storage conditions

Keep in cool and well ventilated area. Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs.

7.2.2. Packaging materials

-

7.2.3. Requirements for storage rooms and vessels

-

7.2.4. Storage class

-

7.2.5. Further information on storage conditions

-

7.3. Specific end use(s)

Recommendations

-

Product name: **9050 X5 HS Clear Coat**

Creation date: **17.12.2013** · Revision: **10.6.2019** · Version: **1**

Industrial sector specific solutions

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

8.1.1. Occupational exposure limit values

Name (CAS)	Limit values		Short-term exposure limit		Remarks	Biological Tolerance Values
	ml/m ³ (ppm)	mg/m ³	ml/m ³ (ppm)	mg/m ³		
Acetone (67-64-1)	500	1210	1500	3620		
2-Butoxyethyl acetate (112-07-2)	20	133	50	332	Sk	
Butyl acetate (123-86-4)	150	724	200	966		
1-Methoxypropyl acetate (108-65-6)	50	274	100	548	Sk	
2-Methylpropan-2-ol (75-65-0)	100	308	150	462		

8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

8.1.3. DNEL/DMEL values

For components

Name	Type	Exposure route	Exposure frequency	Value	Remark
n-butyl acetate (123-86-4)	Consumer	inhalation	long term (systemic effects)	102,34 mg/m ³	
n-butyl acetate (123-86-4)	Consumer	inhalation	long term (systemic effects)	102,34 mg/m ³	
n-butyl acetate (123-86-4)	Consumer	inhalation	short term (systemic effects)	859,7 mg/m ³	
n-butyl acetate (123-86-4)	Consumer	inhalation	short term (systemic effects)	859,7 mg/m ³	
n-butyl acetate (123-86-4)	Worker	inhalation	long term (systemic effects)	480 mg/m ³	
n-butyl acetate (123-86-4)	Worker	inhalation	short term (systemic effects)	480 mg/m ³	
n-butyl acetate (123-86-4)	Worker	inhalation	short term (systemic effects)	960 mg/m ³	
2-methoxy-1-methylethyl acetate (108-65-6)	Consumer	dermal	long term (systemic effects)	54,8 mg/kg	
2-methoxy-1-methylethyl acetate (108-65-6)	Consumer	inhalation	long term (systemic effects)	33 mg/m ³	
2-methoxy-1-methylethyl acetate (108-65-6)	Consumer	oral	long term (systemic effects)	1,67 mg/kg	
2-methoxy-1-methylethyl acetate (108-65-6)	Worker	dermal	long term (systemic effects)	153,5 mg/kg	
2-methoxy-1-methylethyl acetate (108-65-6)	Worker	inhalation	long term (systemic effects)	275 mg/m ³	
acetone (67-64-1)	Worker	dermal	long term (systemic effects)	186 mg/kg	
acetone (67-64-1)	Worker	inhalation	short term (systemic effects)	2420 mg/m ³	
acetone (67-64-1)	Worker	inhalation	long term (systemic effects)	1210 mg/m ³	
acetone (67-64-1)	Consumer	oral	long term (systemic effects)	62 mg/kg	
acetone (67-64-1)	Consumer	dermal	long term (systemic effects)	62 mg/kg	
acetone (67-64-1)	Consumer	inhalation	long term (systemic effects)	200 mg/m ³	

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 9050 X5 HS Clear Coat

Creation date: 17.12.2013 · Revision: 10.6.2019 · Version: 1

8.1.4. PNEC values

For components

Name	Exposure route	Value	Remark
n-butyl acetate (123-86-4)	soil	0,0903 mg/kg	
n-butyl acetate (123-86-4)	fresh water	0,18 mg/L	
n-butyl acetate (123-86-4)	fresh water sediment	0,981 mg/kg	
n-butyl acetate (123-86-4)	marine water	0,018 mg/L	
n-butyl acetate (123-86-4)	marine water sediment	0,0981 mg/kg	
2-methoxy-1-methylethyl acetate (108-65-6)	soil	0,29 mg/kg	
2-methoxy-1-methylethyl acetate (108-65-6)	fresh water	0,635 mg/L	
2-methoxy-1-methylethyl acetate (108-65-6)	fresh water sediment	3,29 mg/kg	
2-methoxy-1-methylethyl acetate (108-65-6)	marine water	0,0635 mg/L	
2-methoxy-1-methylethyl acetate (108-65-6)	marine water sediment	0,329 mg/kg	
acetone (67-64-1)	marine water	1,06 mg/L	
acetone (67-64-1)	fresh water	10,6 mg/L	
acetone (67-64-1)	fresh water sediment	30,4 mg/L	
acetone (67-64-1)	marine water sediment	3,04 mg/L	
acetone (67-64-1)	soil	0,112 mg/L	
acetone (67-64-1)	water treatment plant	29,5 mg/L	

8.2. Exposure controls

8.2.1. Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

8.2.2. Personal protective equipment

Eye and face protection

Safety glasses with side protection (EN 166).

Hand protection

Protective gloves (EN 374).

Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387).

Thermal hazards

-

8.2.3. Environmental exposure controls

-

SAFETY DATA SHEET according to Regulation 1907/2006

Product name: 9050 X5 HS Clear Coat

Creation date: 17.12.2013 · Revision: 10.6.2019 · Version: 1



SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

- Physical state:	liquid
- Colour:	
- Odour:	

Important health, safety and environmental information

- pH	No information.
- Melting point/freezing point	No information.
- Initial boiling point/boiling range	No information.
- Flash point	≤ 56 °C
- Evaporation rate	No information.
- Flammability (solid, gas)	No information.
- Explosion limits (vol%)	No information.
- Vapour pressure	No information.
- Vapour density	No information.
- Density	Density: 0,96 – 1 g/cm ³
- Solubility	No information.
- Partition coefficient	No information.
- Auto-ignition temperature	No information.
- Decomposition temperature	No information.
- Viscosity	No information.
- Explosive properties	No information.
- Oxidising properties	No information.

9.2. Other information

- Remarks:	
------------	--

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

-

10.2. Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3. Possibility of hazardous reactions

-

10.4. Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks.

10.5. Incompatible materials

Oxidants.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 9050 X5 HS Clear Coat

Creation date: 17.12.2013 · Revision: 10.6.2019 · Version: 1

10.6. Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

(a) Acute toxicity

Name	Exposure route	Type	Species	Time	Value	Method	Remark
2-methoxy-1-methylethyl acetate (108-65-6)	dermal	LD ₅₀	rat		5000 mg/kg		
2-methoxy-1-methylethyl acetate (108-65-6)	oral	LD ₅₀	rat		8532 mg/kg		
2-butoxyethyl acetate (112-07-2)	dermal	LD ₅₀	rat		1580 mg/kg		
acetone (67-64-1)	oral	LD ₅₀	rat		5800 mg/kg		
acetone (67-64-1)	dermal	LD ₅₀	rabbit		20000 mg/kg		
2-methylpropan-2-ol (75-65-0)	oral	LD ₅₀	rat		3500 mg/kg		

(b) Skin corrosion/irritation

No information.

(c) Serious eye damage/irritation

Name	Species	Time	Result	Method	Remark
2-methoxy-1-methylethyl acetate (108-65-6)			May cause irritation.		

(d) Respiratory or skin sensitisation

No information.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

No information.

(h) STOT-single exposure

No information.

(i) STOT-repeated exposure

No information.

(j) Aspiration hazard

No information.

SAFETY DATA SHEET according to Regulation 1907/2006

Product name: 9050 X5 HS Clear Coat

Creation date: 17.12.2013 · Revision: 10.6.2019 · Version: 1



SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Acute (short-term) toxicity

For components

Substance (CAS Nr.)	Type	Value	Exposure time	Species	Organism	Method	Remark
n-butyl acetate (123-86-4)	EC ₅₀	44 mg/L	48 h	crustacea			
2-methoxy-1-methylethyl acetate (108-65-6)	LC ₅₀	100 mg/L	96 h	fish	<i>Oncorhynchus mykiss</i>		
	EC ₅₀	500 mg/L	48 h	crustacea			
2-butoxyethyl acetate (112-07-2)	EC ₅₀	150 mg/L	48 h	crustacea			
	EC ₅₀	500 mg/L	72 h	algae			
	LC ₅₀	80 mg/L	96 h	fish			
	EC ₅₀	2800 mg/L	0	bacteria			
acetone (67-64-1)	EC ₅₀	39 mg/L	48 h	crustacea			
	LC ₅₀	5000 mg/L	96 h	fish			

12.1.2. Chronic (long-term) toxicity

For components

Substance (CAS Nr.)	Type	Value	Exposure time	Species	Organism	Method	Remark
acetone (67-64-1)	LC ₅₀	4042 mg/l	14 days	fish			
	NOEC	3400 mg/l	48 h	algae	<i>Pseudokirchneriella subcapitata</i>		

12.2. Persistence and degradability

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

12.2.2. Biodegradation

No information.

12.3. Bioaccumulative potential

12.3.1. Partition coefficient

No information.

12.3.2. Bioconcentration factor (BCF)

No information.

12.4. Mobility in soil

12.4.1. Known or predicted distribution to environmental compartments

No information.

12.4.2. Surface tension

No information.

12.4.3. Adsorption/Desorption

No information.

12.5. Results of PBT and vPvB assessment

No evaluation.

12.6. Other adverse effects

No information.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 9050 X5 HS Clear Coat

Creation date: 17.12.2013 · Revision: 10.6.2019 · Version: 1

12.7. Additional information

For product

Do not allow to reach ground water, water courses or sewage system.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

13.1.1. Product / Packaging disposal

Waste chemical

Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste.

Packaging

Deliver completely emptied containers to approved waste disposal authorities.

13.1.2. Waste treatment-relevant information

-

13.1.3. Sewage disposal-relevant information

-

13.1.4. Other disposal recommendations

-

SECTION 14. TRANSPORT INFORMATION

14.1. UN number

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

3

14.4. Packing group

III

14.5. Environmental hazards

NO.

14.6. Special precautions for user

Limited quantities

5 L

Tunnel restriction code

(D/E)

IMDG flashpoint

56 °C, c.c.

IMDG EmS

F-E, S-E



14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Goods may not be carried in bulk in bulk containers, containers or vehicles.

SAFETY DATA SHEET according to Regulation 1907/2006

Product name: **9050 X5 HS Clear Coat**

Creation date: **17.12.2013** · Revision: **10.6.2019** · Version: **1**



SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)
- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

EU limit values and category: B(e) 840 g/l. VOC Content: 577 g/l

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

Indication of changes

-

Abbreviations and acronyms

ATE - Acute Toxicity Estimate
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
CEN - European Committee for Standardisation
C&L - Classification and Labelling
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
CAS# - Chemical Abstracts Service number
CMR - Carcinogen, Mutagen, or Reproductive Toxicant
CSA - Chemical Safety Assessment
CSR - Chemical Safety Report
DMEL - Derived Minimal Effect Level
DNEL - Derived No Effect Level
DPD - Dangerous Preparations Directive 1999/45/EC
DSD - Dangerous Substances Directive 67/548/EEC
DU - Downstream User
EC - European Community
ECHA - European Chemicals Agency
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)
EEC - European Economic Community
EINECS - European Inventory of Existing Commercial Substances
ELINCS - European List of notified Chemical Substances
EN - European Standard
EQS - Environmental Quality Standard
EU - European Union
Euphrac - European Phrase Catalogue
EWC - European Waste Catalogue (replaced by LoW – see below)
GES - Generic Exposure Scenario
GHS - Globally Harmonized System
IATA - International Air Transport Association
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG - International Maritime Dangerous Goods
IMSBC - International Maritime Solid Bulk Cargoes
IT - Information Technology
IUCLID - International Uniform Chemical Information Database
IUPAC - International Union for Pure Applied Chemistry
JRC - Joint Research Centre
Kow - octanol-water partition coefficient

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **9050 X5 HS Clear Coat**

Creation date: **17.12.2013** · Revision: **10.6.2019** · Version: **1**

LC₅₀ - Lethal Concentration to 50 % of a test population
LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose)
LE - Legal Entity
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
LR - Lead Registrant
M/I - Manufacturer / Importer
MS - Member States
MSDS - Material Safety Data Sheet
OC - Operational Conditions
OECD - Organization for Economic Co-operation and Development
OEL - Occupational Exposure Limit
OJ - Official Journal
OR - Only Representative
OSHA - European Agency for Safety and Health at work
PBT - Persistent, Bioaccumulative and Toxic substance
PEC - Predicted Effect Concentration
PNEC(s) - Predicted No Effect Concentration(s)
PPE - Personal Protection Equipment
(Q)SAR - Qualitative Structure Activity Relationship
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
RIP - REACH Implementation Project
RMM - Risk Management Measure
SCBA - Self-Contained Breathing Apparatus
SDS - Safety data sheet
SIEF - Substance Information Exchange Forum
SME - Small and Medium sized Enterprises
STOT - Specific Target Organ Toxicity
(STOT) RE - Repeated Exposure
(STOT) SE - Single Exposure
SVHC - Substances of Very High Concern
UN - United Nations
vPvB - Very Persistent and Very Bioaccumulative

Key literature references and sources for data

-

List of relevant H phrases

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.



- Provided correct labelling of the product
- Compliance with the local legislation
- Provided correct classification of the product
- Provided adequate transport data

© BENS Consulting | www.bens-consulting.com

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **9050 X5 HS Clear Coat**

Creation date: **17.12.2013** · Revision: **10.6.2019** · Version: **1**

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.