

9150 X15 Lumina

UHS 420 rapid clear coat

silco®

- / Superior finish meets unparalleled efficiency
- / High gloss and quick drying time at room or elevated temperatures
- / Specially developed to replicate the original OEM structure
- / Enhances vehicle appearance with a showroom-quality shine
- / Versatile application over various basecoat systems for different paint jobs
- / Flexible use in different ambient conditions, boosting auto shop productivity

www.silco.si



9150 X15 Lumina

UHS 420 rapid clear coat

Experience the ultimate blend of speed and quality where superior finish meets unparalleled efficiency.

Product info

X15 Lumina is a premium UHS 2K acrylic clear coat characterized with its high level of gloss and quick drying time. It was specially developed to replicate the original OEM structure on new or old cars enhancing the vehicle's appearance with a showroom-quality shine.

It delivers excellent performance when applied over various basecoat systems making it versatile across different types of paint jobs, providing flexibility for auto shops.

Fast drying at room temperature or drying at elevated temperatures maximizes productivity by reducing wait times, allowing for quicker job turnaround.

Long potlife and possibility to choose from three different hardeners and 3 different thinners allows the use of X15 Lumina in different ambient conditions.

Mixing ratio 2:1

Hardener	Fast 9330	Standard 9350	Slow 9370
Drying time*			
20°C/68°F	3 h	3-4 h	4 h
40°C/104°F	20-25 min	25-30 min	30-35 min
60°C/140°F	10-15 min	15 min	20 min
Flash-off 20°C/68°F	5-10 min		
Potlife 20°C/68°F	60 min	60 min	60 min
Thinner	5-10 % (7050 Standard, 7070 Slow)		

*Indicative times subject to hardener and thinner type/application/environment...

Packaging

9150 X15 Lumina
UHS 420 rapid clear coat

Prod. Nr.	Content
9150-1	1 L
9150-5	5 L

Hardener / 9330 - 9370 UHS Hardener
UHS Acrylic Hardener - mixing ratio 2:1

Prod. Nr.	Content	Description
9330-0,5 / 9330-2,5	500 ml / 2.5 L	Fast
9350-0,5 / 9350-2,5	500 ml / 2.5 L	Standard
9370-0,5 / 9370-2,5	500 ml / 2.5 L	Slow