



EN TECHNICAL DATA SHEET

DESCRIPTION

Stripping Gel for the removal of paints, primers, fillers, and powder coatings.

APPLICATION

The Stripping Gel is a product designed for the stripping of all types of paint on surfaces that require the use of a viscous product. It can be applied to vertical surfaces without causing drips.

PROPERTIES

It is a fast-acting and efficient product on most organic coatings, including architectural paints, oil stains, rubber, ink, varnish, etc.

The product is supplied ready to use.

It is compatible with a wide range of materials such as many types of plastic (excluding those with very low resistance to solvents like PC, ABS, or polyacrylate), stone, plaster, glass, wood, and both ferrous and light metals.

APPLICATION METHOD

It is recommended to apply a thick layer using a brush, spatula, paintbrush, or roller. The product should be used undiluted at room temperature. The approximate working time is 20 minutes, although this will depend on the thickness and nature of the coating to be removed, as well as its curing conditions.

The product should not be allowed to dry during the process. Before repainting, ensure the surface is clean and dry. Rinsing with water to remove any residual product is possible but not mandatory.

Tools should be cleaned after the application of the product.

STORAGE

The product should be stored between 5°C and 30°C, protected from moisture and direct sunlight.

SAFETY INFORMATION

Refer to the Safety Data Sheet. For professional use only.

PACKAGING AVAILABLE

Code	Description	Packaging
5015-000002	STRIPPING GEL	5KG

*If you would like more information about our products or means of application, please visit our website www.carrepairsystem.eu or send us an e-mail to info@carrepairsystem.eu.

Technical specifications and suggestions are based on our own experience. We guarantee perfect product quality. However, considering that the conditions of each specific use are beyond our control, we cannot be held responsible for the results obtained.